

SUN2000-30/36/40KTL-M3 Smart PV Controller



Smart

8 strings intelligent monitoring



Efficient

Max. efficiency 98.7%



Safe


Fuse free design



Reliable


Type II surge arresters for DC & AC

Efficiency Curve



SUN2000-30/36/40KTL-M3

Circuit Diagram



SUN2000-30/36/40KTL-M3

Technical Specification

Technical Specification		SUN2000-30KTL-M3	SUN2000-36KTL-M3	SUN2000-40KTL-M3
Efficiency				
Max. Efficiency	98.7%			
European Efficiency	98.4%			
Input				
Max. Input Voltage ¹	1,100 V			
Max. Current per MPPT	26 A			
Max. Short Circuit Current per MPPT	40 A			
Start Voltage	200 V			
MPPT Operating Voltage Range ²	200 V ~ 1000 V			
Rated Input Voltage	600 V			
Number of Inputs	8			
Number of MPP Trackers	4			
Output				
Rated AC Active Power	30,000 W	36,000 W	40,000 W	
Max. AC Apparent Power	33,000 VA ³	40,000 VA	44,000 VA	
Rated Output Voltage	230 Vac / 400 Vac / 480 Vac, 3W/N+PE			
Rated AC Grid Frequency	50 Hz / 60 Hz			
Rated Output Current	43.3 A	52.0 A	57.8 A	
Max. Output Current	47.9 A	58.0 A	63.8 A	
Adjustable Power Factor Range	0.8 LG ... 0.8 LD			
Max. Total Harmonic Distortion	< 3%			
Protection				
Input-side Disconnection Device	Yes			
Anti-islanding Protection	Yes			
AC Overcurrent Protection	Yes			
DC Reverse-polarity Protection	Yes			
PV-array String Fault Monitoring	Yes			
DC Surge Arrester	Yes			
AC Surge Arrester	Yes			
DC Insulation Resistance Detection	Yes			
Residual Current Monitoring Unit	Yes			
Arc Fault Protection	Yes			
Ripple Receiver Control	Yes			
Integrated PID Recovery ⁴	Yes			
Communication				
Display	LED Indicators, Integrated WLAN + FusionSolar APP			
RS485	Yes			
Smart Dongle	WLAN/Ethernet via Smart Dongle-WLAN-FE (Optional) 4G / 3G / 2G via Smart Dongle-4G (Optional)			
Monitoring BUS (MBUS)	Yes (Isolation Transformer required)			
General Data				
Dimensions (W x H x D)	640 x 530 x 270 mm (25.2 x 20.9 x 10.6 inch)			
Weight (with mounting plate)	43 kg (94.8 lb)			
Operating Temperature Range	-25 ~ + 60 °C (-13 °F ~ 140 °F)			
Cooling Method	Natural Convection			
Max. Operating Altitude	4,000 m (13,123 ft.) (Derating above 2000 m)			
Relative Humidity	0% RH ~ 100% RH			
DC Connector	Staubli MC4			
AC Connector	Waterproof Connector + OT/DT Terminal			
Protection Degree	IP 66			
Topology	Transformerless			
Nighttime Power Consumption	≤ 5.5W			
Optimizer Compatibility				
DC MBUS Compatible Optimizer	SUN2000-450W-P			
Standard Compliance (more available upon request)				
Safety	EN 62109-1/-2, IEC 62109-1/-2, EN 50530, IEC 62116, IEC 60068, IEC 61683			
Grid Connection Standards	IEC 61727, VDE-AR-N4105, VDE 0126-1-1, BDEW, G59/3, UTE C 15-712-1, CEI 0-16, CEI 0-21, RD 661, RD 1699, P.O. 12.3,RD 413, EN-50438-Turkey, EN-50438-Ireland, C10/11, MEA, Resolution No.7, NRS 097-2-1, AS/NZS 4777.2, DEWA			

1. The maximum input voltage is the upper limit of the DC voltage. Any higher input DC voltage would probably damage inverter.

2. Any DC input voltage beyond the operating voltage range may result in inverter improper operating.

3. For Austria, German, Belgium & Ukraine the Max. AC Apparent Power will not exceed 30,000 VA (with regard to grid code: VDE-AR-N-4105, C10/11 & Austria)

4. SUN2000-30~40KTL-M3 raises potential between PV- and ground to above zero through integrated PID recovery function to recover module degradation from PID. Supported module types include: P-type (mono, poly), N-type (nPERT, HIT)