

28 Ports Full Giga PoE Switch with 2 SFP slot

24*1000M POE + 2*GE + 2*GF SFP uplink

EWIND



- 24*10/100/1000M POE + 2*10/100/1000M RJ45 + 2*100/1000M SFP Port PoE Switch; Ports 1-24 support POE IEEE 802.3af/at;
- Comply with IEEE 802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3z standards;
- PoE port support AF/AT intelligent recognition. Standard power is 15.4W/port, Maximum power: 30W/port;
- **Support AI Watchdog, Port self-healing, VLAN, extend 300meter distance, Auto Speed Change, Priority port & reduce the after-resale;**
- Supports POE devices such as wireless access points (APs) and network surveillance cameras through Category 5/6 Ethernet cables;
- The power supply total is 400W;
- 3 years warranty.

RoHS **FC** **CE**

Introduction

The EW-S1928CG-AP-AT series is an unmanaged PoE switch featuring 24 x 10/100/1000M PoE ports, 2 x 1000M uplink RJ45 ports, and 2 x 100/1000M SFP ports. Ports 1-24 support IEEE 802.3af/at PoE standards, with each port capable of delivering up to 30W, and a maximum total PoE output of 400W. As a PoE power supply device, it automatically detects and recognizes compatible powered devices, supplying power through the network cable. It can power PoE-enabled devices such as wireless APs, IP cameras, VoIP phones, and video intercoms. This switch is ideal for high-density PoE environments, such as hotels, campuses, factories, and small to medium-sized enterprises, providing an economical and efficient network solution.


TECHNICAL SPECIFICATION

| Model | EW-S1928CG-AP-AT |
|------------|--|
| Fixed Port | 24*10/100/1000 Base-T/TX PoE ports (Data/Power) 2*10/100/1000Base-T/TX RJ45 ports (Data) 2*1000Base-X uplink SFP fiber slot ports (Data) |
| POE Port | Port 1-24 support PoE @ IEEE802.3af/at |

| | |
|------------------------------|---|
| Feature | <p>With the Dial code switch, support port priority by default.</p> <p>E: AI Extend 300meters transmission and auto speed change of single port (limit 10Mbps), other ports maintain 1000M within 100 meters;</p> <p>V: Turn on, 1-24 Port support each port Isolation & VLAN;</p> <p>D: Turn on, 1-24 Port support AI-PoE Network self-healing mode (PoE Watchdog function), Automatic solve the camera problem & reduce after-sale.</p> |
| Fan | Non-Fan, silent working status can satisfy more users with different requirement. |
| Network Protocol | <p>IEEE802.3 10BASE-T; IEEE802.3i 10Base-T;</p> <p>IEEE802.3u 100Base-TX;</p> <p>IEEE802.3ab 1000Base-T;</p> <p>IEEE802.3z 1000base-X;</p> <p>IEEE802.3u 100Base-FX;</p> <p>IEEE802.3x.</p> |
| PoE Standard | IEEE802.3af/at |
| Ethernet Port Feature | 10/100/1000Base-T(X) automatic detection, full/half Duplex MDI/MDI-X adaptive |
| Fiber Port Feature | Gigabit SFP Port (Fiber module is not included, need to order separately, module options include single/multi-mode, single/dual fiber, LC) |
| Fiber Port Feature | Store and Forward |
| Switching Capacity | 56Gbps (non-blocking) |
| Forwarding Mode | 41.664Mpps |
| MAC | 8K |
| Buffer Memory | 4M |
| Twisted Pair Transmission | <p>10BASE-T: Cat5 UTP (≤300 meter)</p> <p>100BASE-TX: Cat5 or later UTP (≤100 meter)</p> <p>1000BASE-TX: Cat5 or later UTP (≤100 meter)</p> |
| Power Supply Pin | Default 1/2(+), 3/6(-); |
| MAX / AVERAGE Power Per Port | 30W/15.4W |
| Total PWR / Input Voltage | 400W (100-240V) |
| Power Consumption | Standby:<5W; Full load:<400W |
| LED Indicator | <p>Power indicator: PWR (Green);</p> <p>Network indicator: 1-24(Link/Act)/ (Green), 25-28(Link/Act)/ (Green)</p> |
| Power Supply | Built in switching power supply, AC100~240V 50-60Hz |

| | |
|---------------------------|---|
| Operation TEMP / Humidity | -20~+55°C;5%~90% RH non condensing |
| Storage TEMP / Humidity | -40~+75°C;5%~95% RH non condensing |
| Dimension | 440*190*44mm |
| Net /Gross Weight | <3kg / <4kg |
| Installation Method | desktop type, wall mounted,19-inch 1U cabinet installation |
| Protection | IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-5(Lightning protection/Surge): Power:CM±4kV/DM±2kV; Port: ±4kV |
| Protection Level | IP30 |
| Certification | CCC; CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS |
| Warranty | 3 years, lifetime maintenance. |

DIMENSION



APPLICATION



PACKING LIST

| CONTENT | QTY | UNIT |
|--|-----|------|
| 28 Ports Full Gigabit PoE Switch (EW-S1928CG-AP-AT) | 1 | SET |
| AC Power cord | 1 | PC |
| Hanging Ear | 1 | PAIR |
| User Guide | 1 | PC |
| Warranty Card | 1 | PC |