

DS-2CD1621FWD-I (Z) 2.0 MP CMOS Vari-Focal Network Bullet Camera



Key Features

- 1/2.8" progressive scan CMOS
- Up to 2.0 megapixel
- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens
- Up to 30 m IR range
- Dual stream
- 120 dB WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- PoE (Power over Ethernet)
- IP67
- Mobile monitoring via Hik-Connect




Specification

| Camera | |
|-------------------------------|---|
| Image Sensor | 1/2.8" progressive scan CMOS |
| Min. Illumination | Color: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR |
| Shutter Speed | 1/3 s to 1/100, 000 s, support slow shutter |
| Lens | 2.8 mm to 12 mm @F1.4 , horizontal field of view: 100° to 35° |
| Lens Mount | Φ14 |
| Day & Night | IR cut filter with auto switch |
| 3-Axis Adjustment | Pan: 0° to 355°, tilt: 0° to 100°, rotation: 0° to 355° |
| DNR (Digital Noise Reduction) | 3D DNR |
| WDR (Wide Dynamic Range) | 120 dB |
| Compression Standard | |
| Video Compression | Main stream: H.264+/H.264 Sub stream: H.264/MJPEG |
| H.264 Type | Baseline profile/Main profile |
| Video Bit Rate | 32 Kbps to 8 Mbps |
| Dual Stream | Support |
| Image | |
| Max. Resolution | 1920 × 1080 |
| Main Stream | 50Hz: 25fps @(1920 × 1080, 1280 × 960, 1280 × 720) |
| Max. Frame Rate | 60Hz: 30fps @(1920 × 1080, 1280 × 960, 1280 × 720) |
| Sub-stream | 50Hz: 25fps @(704 × 576, 640 × 480, 352 × 288, 320 × 240) |
| Max. Frame Rate | 60Hz: 30fps @(704 × 480, 640 × 480, 352 × 240, 320 × 240) |
| Image Settings | Brightness, saturation, contrast, sharpness are adjustable via web browser or client software |
| Day/Night Switch | Support auto, scheduled |
| Others | Mirror, BLC (area configurable), region of interest (support 1 fixed region) |
| Network | |
| Network Storage | Support micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS, SMB/CIFS), ANR |
| Detections | Motion detection |
| Alarms | Video tampering, network disconnected, IP address conflicted, HDD full, HDD error |
| Protocols | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, Bonjour |
| Standard | ONVIF (PROFILE S, PROFILE G), ISAPI |
| General Function | One-key rest, anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter |
| Interface | |
| Communication Interface | 1 RJ45 10M/100M self-adaptive Ethernet port |
| Video Output (Without -Z) | 1Vp-p composite output (75Ω/BNC) |
| Reset | Support |
| General | |
| Operating Conditions | -30 °C to 60°C (-22 °F to 140°F), humidity: 95% or less (non-condensing) |
| Power Supply | DC12V ± 25%, PoE (802.3af) |
| Power Consumption | Max. 5.5 W/11 W (with -Z) |
| Ingress Protection | IP 67 |
| IR Range | Up to 30 m |
| Dimensions | 91.6 mm × 105 mm × 294.5 mm (3.6" × 4.1" × 11.6") |
| Weight | 1200 g (2.6 lb.) |

Available Models

DS-2CD1621FWD-I (Z)

Dimension



Accessory



DS-1260ZJ
Junction Box



DS-1275ZJ
Vertical Pole Mounting Bracket



DS-1280ZJ-S
Junction Box



DS-1276ZJ
Corner Mounting Bracket

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (0) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com